



Provincial Recreation Vehicle Regulations

revised September 2016

Province or Territory	Maximum Length		Vehicle Combination		Max Height	Max Width	Passengers in Towed RVs	Passengers in Seat Belts	Propane on while Travelling	Passengers allowed in Truck Camper	# of safety Chains or attachments required towing RV Trailer
	Motor Homes	Towables	Max Length	# of Units							
AB	14m	12.5m	20m	3 μ	4.15m	2.6m	No	Yes	NR	No	0 - 2 ϵ
BC	14m ¹	12.5m	20m	2	4.15m	2.6m	No	Yes	Yes *	No	1
MB	14m ¹	12.5m	21.5m or 23m \S	2 or 3 \S	4.15m	2.6m	No	Yes	Yes	Yes	1
NB	14m	12.5m β	23m	2	4.15m	2.6m	No	Yes	NR	Yes	2 ϵ
NL	12.5m ¹ ; 14.0 m ^{^1}	12.5m ¹ ; 14.0 m ^{^1}	23m β	2	4.15m	2.6m	No	Yes	NR	NR	1 ϵ
NS	14m	12.5m	23m	2	4.15m	2.6m	No	Yes	Yes α	Yes \dagger	2
NU	12.5m β^1	NR	21m	2	4.2m	2.6m	No	Yes	NR	Yes	NS
NWT	14m β^1	NR	20m	2	4.2m	2.6m	No	Yes	NR	No	NR
ON	14m ¹	12.5m	23m	3	4.15m	2.6m	No	Yes	Yes	Yes	1
PEI	14m	12.5m	23m	2	4.15m	2.6m	NS	Yes #	NS	NS	2
QC	14m β^1	12.5m	19m or 23m \ddagger	3 or 2 \ddagger	4.15m	2.6m	No	Yes	Yes	Yes	1
SK	14m ¹	12.5m	23m	3 Υ	4.15m	2.6m	No	Yes	NR	Yes	2
YT	14m ¹	12.5m	25m	3 μ	4.2m	2.6m	No	Yes # β	NR β	NR β	2

β - under review \S - 23m if 1st is 5th wheel * - ICBC Regulations \ddagger - seat belts on NS - not specified NR - not required or regulated # - where available
 α - providing there is a cut-off valve \wedge - 14 m allowed with tandem axles; 12.5m if no tandem axles

ϵ - **AB**: A 5th wheel does not require a secondary means of attachment. **Other trailers: AB**: Two separate means of attachment required. SAE recommends chains crossing under the hitch and able to keep the unit substantially following the towing vehicle. Each chain must be able to tow the unit if the other fails and keep hitch off the road. **NB**: Two separate means of attachment required, so constructed and attached that the failure of one will not permit the towed unit to become detached. **NL**: Chain or cable must be equal in strength to the principal coupling device.

\ddagger - Maximum Length for a 2-unit combination is 23 m when the length of the motor vehicle is 12.5 m and less; and 19 m when the length of the motor vehicle is between 12.5m and 14m.

Υ - if lead trailer is a semi-trailer, gooseneck trailer (may be equipped with ball or pin type hitch), or has two or more axles in tandem

μ - Lead trailer must be a 5th wheel (AB specifies "pin & plate 5th wheel coupling mounted over the rear axle"); must have two or more tandem axles; and must be longer than following unit.

¹: See page 2 for specific notes on 14-metre regulation / legislation changes, and interim permits where applicable.